

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part B

Revision date: 19.06.2023

Page 1 of 17

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ARC 797(E) Part B

UFI: OGS4-5MAE-3TM2-Y782

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

ARC Polymer Composite. Repair damage caused by impact, abrasion or erosion and chemical attack.

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name:	Chesterton International GmbH	
Street:	Am Lenzenfleck 23	
Place:	D-85737 Ismaning GERMANY	
Telephone:	+49 89 99 65 46 - 0	Telefax: +49 89 99 65 46 - 50
e-mail:	eu-sds@chesterton.com	
Contact person:	eu-sds@chesterton.com	Telephone: +49 89 99 65 46 - 0
e-mail:	eu-sds@chesterton.com	
Internet:	www.chesterton.com	
Responsible Department:	eu-sds@chesterton.com	

1.4. Emergency telephone number:

+49(0) 551 - 1 92 40 (GIZ-Nord, 24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Acute Tox. 4; H302
Acute Tox. 4; H332
Skin Corr. 1; H314
Eye Dam. 1; H318
Skin Sens. 1; H317

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

benzyl alcohol
3-aminomethyl-3,5,5-trimethylcyclohexylamine
2-methylpentane-1,5-diamine

Signal word: Danger

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part B

Revision date: 19.06.2023

Page 2 of 17

Pictograms:



Hazard statements

H302+H332 Harmful if swallowed or if inhaled.
 H314 Causes severe skin burns and eye damage.
 H317 May cause an allergic skin reaction.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER/doctor.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Quantity
	EC No	Index No
	REACH No	
	Classification (Regulation (EC) No 1272/2008)	
100-51-6	benzyl alcohol	25 -< 50 %
	202-859-9	603-057-00-5
		01-2119492630-38
	Acute Tox. 4, Acute Tox. 4, Eye Irrit. 2; H332 H302 H319	
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	25 -< 50 %
	220-666-8	612-067-00-9
		01-2119514687-32
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1A; H312 H302 H314 H318 H317	
15520-10-2	2-methylpentane-1,5-diamine	5 -< 10 %
	239-556-6	
		01-2119976310-41
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1, Eye Dam. 1, STOT SE 3; H332 H312 H302 H314 H318 H335	

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part B

Revision date: 19.06.2023

Page 3 of 17

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
100-51-6	202-859-9	benzyl alcohol	25 -< 50 %
		inhalation: LC50 = 11 mg/l (vapours); inhalation: LC50 = > 4,178 mg/l (dusts or mists); oral: LD50 = 1230 mg/kg	
2855-13-2	220-666-8	3-aminomethyl-3,5,5-trimethylcyclohexylamine	25 -< 50 %
		dermal: ATE = 1100 mg/kg; oral: ATE 1030 mg/kg Skin Sens. 1A; H317: >= 0,001 - 100	
15520-10-2	239-556-6	2-methylpentane-1,5-diamine	5 -< 10 %
		inhalation: LC50 = 11 mg/l (vapours); inhalation: LC50 = 4,9 mg/l (dusts or mists); dermal: LD50 = 1870 mg/kg; oral: LD50 = 1170 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!

Remove affected person from the danger area and lay down. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Remove casualty to fresh air and keep warm and at rest. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. Immediate medical treatment required because corrosive injuries that are not treated are hard to cure.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Let water be drunken in little sips (dilution effect). Do NOT induce vomiting. Seek medical advice immediately.

4.2. Most important symptoms and effects, both acute and delayed

- Causes severe skin burns and eye damage.
- Allergic reactions
- Gastrointestinal complaints

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part B

Revision date: 19.06.2023

Page 4 of 17

5.1. Extinguishing media

Suitable extinguishing media

- Dry extinguishing powder.
- Carbon dioxide (CO₂).
- alcohol resistant foam.
- Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

- Carbon monoxide
- Carbon dioxide (CO₂).
- Nitrogen oxides (NO_x)

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Safe handling: see section 7

Personal protection equipment: see section 8

Provide adequate ventilation as well as local exhaust at critical locations.

Remove persons to safety.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains. Clean contaminated articles and floor according to the environmental legislation. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part B

Revision date: 19.06.2023

Page 5 of 17

Advice on safe handling

See section 8. Wear personal protection equipment (refer to section 8). People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this mixture.

Avoid contact with skin, eyes and clothes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

When using do not eat, drink or smoke.

Never use pressure to empty container. Keep/Store only in original container.

Do not allow to enter into surface water or drains.

Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

Work in well-ventilated zones or use proper respiratory protection. Only wear fitting, comfortable and clean protective clothing. Avoid contact with skin, eyes and clothes. Wash hands and face before breaks and after work and take a shower if necessary.

Use protective skin cream before handling the product.

Further information on handling

Wash hands before breaks and after work. Used working clothes should not be worn outside the work area.

Street clothing should be stored separately from work clothing.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Keep/Store only in original container.

Hints on joint storage

Keep away from:

- Food and feedingstuffs

Further information on storage conditions

Keep away from:

- Frost
- Heat
- Humidity

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part B

Revision date: 19.06.2023

Page 6 of 17

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
100-51-6	benzyl alcohol			
Worker DNEL, long-term		inhalation	systemic	22 mg/m ³
Worker DNEL, acute		inhalation	systemic	110 mg/m ³
Worker DNEL, long-term		dermal	systemic	8 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	40 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	5,4 mg/m ³
Consumer DNEL, acute		inhalation	systemic	27 mg/m ³
Consumer DNEL, long-term		dermal	systemic	4 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	20 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	4 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	20 mg/kg bw/day
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine			
Consumer DNEL, acute		oral	systemic	0,3 mg/kg bw/day
Worker DNEL, long-term		inhalation	local	0,073 mg/m ³
Worker DNEL, acute		inhalation	local	0,073 mg/m ³
Consumer DNEL, long-term		oral	systemic	0,3 mg/kg bw/day
15520-10-2	2-methylpentane-1,5-diamine			
Worker DNEL, acute		inhalation	local	0,5 mg/m ³
Consumer DNEL, acute		inhalation	local	0,25 mg/m ³
Worker DNEL, long-term		inhalation	local	0,25 mg/m ³
Worker DNEL, long-term		dermal	systemic	1,5 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	0,125 mg/m ³
Consumer DNEL, long-term		dermal	systemic	0,75 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,25 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part B

Revision date: 19.06.2023

Page 7 of 17

PNEC values

CAS No	Substance	Value
Environmental compartment		
100-51-6	benzyl alcohol	
Freshwater		1 mg/l
Freshwater (intermittent releases)		2,3 mg/l
Marine water		0,1 mg/l
Freshwater sediment		5,27 mg/kg
Marine sediment		0,527 mg/kg
Micro-organisms in sewage treatment plants (STP)		39 mg/l
Soil		0,456 mg/kg
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	
Freshwater		0,06 mg/l
Freshwater (intermittent releases)		0,23 mg/l
Marine water		0,006 mg/l
Freshwater sediment		5,784 mg/kg
Marine sediment		0,578 mg/kg
Micro-organisms in sewage treatment plants (STP)		3,18 mg/l
Soil		1,121 mg/kg
15520-10-2	2-methylpentane-1,5-diamine	
Freshwater		0,93 mg/l
Freshwater (intermittent releases)		0,93 mg/l
Marine water		0,093 mg/l
Freshwater sediment		144,7 mg/kg
Marine sediment		14,5 mg/kg
Micro-organisms in sewage treatment plants (STP)		29,1 mg/l
Soil		3,52 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection:

Eye glasses with side protection

goggles

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part B

Revision date: 19.06.2023

Page 8 of 17

Hand protection

Tested protective gloves must be worn: EN ISO 374

NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber)

Thickness of the glove material $\geq 0,4$ mm

Breakthrough times and swelling properties of the material must be taken into consideration.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Wearing time with occasional contact (splashes): max. 480 min. (NBR (Nitrile rubber))

Wearing time with permanent contact 240 - 480 min (NBR (Nitrile rubber))

Observe the wear time limits as specified by the manufacturer.

Skin protection

Protective clothing

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Combination filtering device A-P3

Self-contained respirator (breathing apparatus)

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	transparent	
Odour:	characteristic	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability		
Solid/liquid:		No data available
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		> 83 °C
Auto-ignition temperature:		> 350 °C
Decomposition temperature:		No data available
pH-Value (at 23 °C):		~ 12,1
Solubility in other solvents		
No information available.		
Partition coefficient n-octanol/water:		No data available
Vapour pressure:		No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part B

Revision date: 19.06.2023

Page 9 of 17

Density (at 23 °C): ~ 1,0 g/cm³
Relative vapour density: No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No information available.

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No information available.

Other safety characteristics

Evaporation rate:

No data available

Sublimation point:

No data available

Softening point:

No data available

Pour point:

No data available

Viscosity / dynamic:
(at 23 °C)

~ 300 mPa·s

Further Information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if swallowed.

Harmful if inhaled.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part B

Revision date: 19.06.2023

Page 10 of 17

ATEmix calculated

ATE (oral) 1125,4 mg/kg; ATE (dermal) 2165,6 mg/kg; ATE (inhalation vapour) 20,18 mg/l; ATE (inhalation dust/mist) 2,654 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
100-51-6	benzyl alcohol				
	oral	LD50 1230 mg/kg	Mouse	Cosmet. Toxicol. 11, 1011-1013 (1973) (1)	OECD Guideline 401
	inhalation vapour	LC50 11 mg/l			
	inhalation (4 h) dust/mist	LC50 > 4,178 mg/l	Rat	ECHA	OECD 403
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine				
	oral	ATE 1030 mg/kg			
	dermal	ATE 1100 mg/kg			
15520-10-2	2-methylpentane-1,5-diamine				
	oral	LD50 1170 mg/kg	Rat	Study report (1984)	OECD Guideline 401
	dermal	LD50 1870 mg/kg	Rat	Study report (1978)	OECD Guideline 402
	inhalation vapour	LC50 11 mg/l			
	inhalation (1 h) dust/mist	LC50 4,9 mg/l			

Irritation and corrosivity

Causes severe skin burns and eye damage.
Causes serious eye damage.

Sensitising effects

May cause an allergic skin reaction. (3-aminomethyl-3,5,5-trimethylcyclohexylamine)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part B

Revision date: 19.06.2023

Page 11 of 17

SECTION 12: Ecological information

12.1. Toxicity

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part B

Revision date: 19.06.2023

Page 12 of 17

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
100-51-6	benzyl alcohol					
	Acute fish toxicity	LC50 > 100 mg/l	96 h	Oryzias latipes	Review article or handbook (2009)	OECD Guideline 203
	Acute algae toxicity	ErC50 770 mg/l	72 h	Raphidocelis subcapitata	Review article or handbook (2009)	OECD Guideline 201
	Acute crustacea toxicity	EC50 230 mg/l	48 h	Daphnia magna	Review article or handbook (2009)	OECD Guideline 202
	Fish toxicity	NOEC 48,897 mg/l	30 d	Fish species	http://epa.gov/oppt/exposure/pubs/episui	other: QSAR
	Algae toxicity	NOEC 51 mg/l	3 d			
	Crustacea toxicity	NOEC 51 mg/l	21 d	Daphnia magna	Review article or handbook (2009)	OECD Guideline 211
	Acute bacteria toxicity	(EC50 1385 mg/l)	3 h	activated sludge, domestic	Study report (1989)	OECD Guideline 209
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine					
	Acute fish toxicity	LC50 110 mg/l	96 h	Leuciscus idus	REACH Registration Dossier	EU Method C.1
	Acute algae toxicity	ErC50 37 mg/l	72 h	Desmodesmus subspicatus	REACH Registration Dossier	EU Method C.3
	Acute crustacea toxicity	EL50 23 mg/l	48 h	Daphnia magna	REACH Registration Dossier	OECD Guideline 202
	Crustacea toxicity	NOEC 3 mg/l	21 d	Daphnia magna	REACH Registration Dossier	other: OECD 202, part 2
15520-10-2	2-methylpentane-1,5-diamine					
	Acute fish toxicity	LC50 1825 mg/l	96 h	Pimephales promelas	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Raphidocelis subcapitata	REACH Registration Dossier	EU Method C.3
	Acute crustacea toxicity	EC50 23,4 mg/l	48 h	Daphnia magna	Study report (1985)	OECD Guideline 202
	Crustacea toxicity	NOEC >= 9,3 mg/l	21 d	Daphnia magna	REACH Registration Dossier	EU Method C.20

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part B

Revision date: 19.06.2023

Page 13 of 17

	Acute bacteria toxicity	(EC50 mg/l)	1558	3 h		REACH Registration Dossier	
--	-------------------------	----------------	------	-----	--	----------------------------------	--

12.2. Persistence and degradability

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
100-51-6	benzyl alcohol			
	OECD 301A/ ISO 7827/ EEC 92/69V, C.4-A	95 - 97%	21	
	Readily biodegradable (according to OECD criteria).			
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine			
	OECD 301A/ ISO 7827/ EEC 92/69V, C.4-A	8 %	28	
	Not readily biodegradable (according to OECD criteria)			

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
100-51-6	benzyl alcohol	1
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	0,99
15520-10-2	2-methylpentane-1,5-diamine	0

BCF

CAS No	Chemical name	BCF	Species	Source
100-51-6	benzyl alcohol	1,371	QSAR model	http://epa.gov/oppt/
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	2,63		REACH Registration D

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part B

Revision date: 19.06.2023

Page 14 of 17

Disposal recommendations

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. The waste code has to be identified in agreement with the disposal company or the competent authority.

Contaminated packaging

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 2735
14.2. UN proper shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (Isophoronediamine, 2-methylpentane-1,5-diamine)
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Classification code:	C7
Special Provisions:	274
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	80
Tunnel restriction code:	E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 2735
14.2. UN proper shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (Isophoronediamine, 2-methylpentane-1,5-diamine)
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Classification code:	C7
Special Provisions:	274
Limited quantity:	5 L
Excepted quantity:	E1

Marine transport (IMDG)

14.1. UN number or ID number:	UN 2735
14.2. UN proper shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (Isophoronediamine, 2-methylpentane-1,5-diamine)
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Special Provisions:	223, 274
Limited quantity:	5 L

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part B

Revision date: 19.06.2023

Page 15 of 17

Excepted quantity: E1
EmS: F-A, S-B
Segregation group: 18 - alkalis

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 2735
14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Isophoronediamine, 2-methylpentane-1,5-diamine)
14.3. Transport hazard class(es): 8
14.4. Packing group: III
Hazard label: 8
Special Provisions: A3 A803
Limited quantity Passenger: 1 L
Passenger LQ: Y841
Excepted quantity: E1
IATA-packing instructions - Passenger: 852
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 856
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

2004/42/EC (VOC): < 500 g/l (A&B)
Subcategory according to Directive 2004/42/EC: Two-pack reactive performance coatings for specific end use such as floors - Solvent-borne coatings, VOC limit value: 500 g/l

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

benzyl alcohol
3-aminomethyl-3,5,5-trimethylcyclohexylamine

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part B

Revision date: 19.06.2023

Page 16 of 17

2-methylpentane-1,5-diamine

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,9,11.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer
(Regulations Concerning the International Transport of Dangerous Goods by Rail)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organization
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
SVHC: Substance of Very High Concern

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 797(E) Part B

Revision date: 19.06.2023

Page 17 of 17

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
Acute Tox. 4; H332	Calculation method
Skin Corr. 1; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H302+H332	Harmful if swallowed or if inhaled.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)