

Grease Compatibility

	613	615	622	625	629	630	635	638
Aluminum Complex	I	A	C	A	I	A	A	A
Barium Complex	I	C	I	C	C	C	C	C
Calcium Stearate	A	C	I	C	I	C	C	C
Calcium 12 Hydroxy	C	A	C	A	A	A	A	A
Calcium Complex	I	I	I	I	C	I	I	I
Calcium Sulfonate	A	C	A	C	I	C	C	C
Clay Non-Soap	I	I	I	I	A	I	I	I
Lithium Stearate	C	A	I	A	I	A	A	A
Lithium 12 Hydroxy	C	A	I	A	I	A	A	A
Lithium Complex	C	C	C	C	I	C	C	C
Polyurea, Conventional	I	I	I	I	I	I	I	I
Polyurea, Shear Stable	C	C	C	C	I	C	C	C

Key

- C** Compatible. Grease may be installed directly.
- A** Acceptable. Grease normally. Re-grease if oil bled in 24 hrs.
- I** Incompatible. Old grease must be purged.

Functions of a Lubricant:

- Separation of Parts
- Reduction of Heat
- Contamination Control
- Corrosion Prevention
- Reduce Component Wear
- Support Load

Chesterton ISO certificates available on chesterton.com/corporate/iso

Technical data reflects results of laboratory tests and is intended to indicate general characteristics only. A.W. Chesterton Company disclaims all warranties express or implied, including warranties of merchantability and fitness for a particular purpose. Liability, if any, is limited to product replacement only. Any images contained herein are for general illustrative or aesthetic purposes only and are not intended to convey any instructional, safety, handling or usage information or advice respecting any product or equipment. Please refer to relevant Safety Data Sheets, Product Data Sheets, and/or Product Labels for safe use, storage, handling, and disposal of products, or consult with your local Chesterton sales representative.




© 2024 A.W. Chesterton Company. ® Registered trademark owned by A.W. Chesterton Company in USA and other countries, unless otherwise noted.

A.W. Chesterton Company, 860 Salem Street, Groveland, MA 01834 USA
Telephone: 781-438-7000 chesterton.com

Form No. EN25661 Bearing Reliability Pocket Guide – English 04/24

Bearing Lubrication Quick Reference Guide


- Selection
- Frequency
- Quantity
- Compatibility



Frequency

Re-Greasing Frequency

- 1** Select RPM
- 2** Select shaft diameter
- 3** Frequency/Bearing Type—Hours
- 4** Adjust for Application
Adjusted Frequency = Value **3** x Correction Factor (Cf)



- a** radial ball bearings
- b** cylindrical roller bearings, needle roller bearings
- c** spherical roller bearings, taper roller bearings, thrust ball bearings
- d** bearing bore diameter

Note: Values are based on 60°C (140°F). For increased temperature above 60°C (140°F), reduce 50% for every 10°C (50°F) increase.

Grease Correction Factor by Application


Equipment	Service Conditions	Correction Factor (Cf)
Electric Motors-Horizontal, High Speed Spindles, Machining Centers	Clean, Dry, No Load and Vibration	0.9-1.0
Fans, Blowers-Horizontal, Mixers-Sealed, Split Case Pumps-Sealed Railway	Clean, Dry, Slight Vibration, Slight Dust/Dirt	0.7-0.8
Hammer Mills, Pulverizers, Cranes, Pulleys/Drum, Agitators, Mixers-Horizontal Electric Motors-Mining	High Humidity, Moderate Load and Vibration, Light Dust/Dirt	0.5-0.6
Electric Motors-Belt Drive Cooling Tower, Fin Fans, Paper Machine-Dryers, Stock Chest, Washers, Sag/Ball Mills, Kilns Drives	Occasionally Wet, Moderate Load and Vibration, Moderate Dust/Dirt pH 5-8	0.3-0.4
Agitators, Mixers-Vertical, Belt and Screw Press, Centrifuges, Slurry Pumps, Electric Motors-Vertical, Food Packaging Machinery	Always Wet, Moderate Load and Vibration, Start and Stop pH <4 or >10	0.2-0.3
Belt Conveyors, Paper Machine-Wet End Mining, Construction Equipment Vibrating Motors, Screen	Water Spray, Heavy Load and Vibration, Heavy Abrasive Dust/Dirt	0.1

Initial Fill of Bearing - % Free Space

Grease quantity as a percentage of bearing free space at various speed factors.



Photo courtesy of SKF USA Inc.



Initial Fill of Housing




Photo courtesy of SKF USA Inc.

Lubricating from side:
Fill 40% of housing

Lubricating from center:
Fill 20% of housing

For highly contaminated environments or slow speeds:
Fill up to 80% of housing

Grease Quantity for Refilling

Re-greasing volume based on bearing size and service intervals, for ideal conditions.

For a specific application, use *Re-Greasing Frequency Chart*.





Photo courtesy of SKF USA Inc.


Quantity in grams (g) = B x A x 0.005

If only bearing housing dimensions are known, grams can be estimated by quantity in grams (g) = (W x L)/3 x 0.005


Selection

Speed Factor Determination

$$\text{Speed Factor, NDm} = \text{RPM} \times (D1 + D2) / 2$$



Base Oil Viscosity Determination



Grease Selection Guide

Chesterton Grease	ISO	NDm*	Temp	Water	Load	Oil Bleed	Electric Motors
613	220	1.0 - 4.0	B	B	B	B	NR
615#1, 615#2	100	0.7 - 3.0	B	A	A	A	C
615#2-460	460	<0.5	B	A	A	A	NR
622	100	0.5 - 3.0	B	B	B	B	B
625	100	0.7 - 3.0	B	A	A	A	C
629	200	0.5 - 3.0	A	B	C	A	B
630	46	1.5 - 8.0	A	A	A	A	A
635	100	1.5 - 5.0	A	A	A	A	A
638-46	46	1.5 - 8.0	A	A	A	A	A
638-100	100	1.5 - 5.0	A	A	A	A	A

*NDm X 100K, A=Best B=Good C=Fair NR= Not Recommend

Chesterton Grease	Operating Temperature	DN (Speed Factor)	NLGI #
630, 635, 638-100, 638-46	-34 to 37°C (-30 to 100°F)	0 - 75,000	1
		75,000 - 150,000	2
		150,000 - 300,000	2
613, 615, 622, 625	-34 to 65°C (0 to 150°F)	0 - 75,000	2
		75,000 - 150,000	2
		150,000 - 300,000	3
629, 630, 635, 638-100, 638-46	37 to 135°C (100 to 275°F)	0 - 75,000	2
		75,000 - 150,000	3
		150,000 - 300,000	3

Please contact Chesterton Application Engineering for NLGI #3.

NLGI depends on other factors as well, including bearing type, thickener type, base oil viscosity, and base oil type.